



The IKA® LR-2.ST system is a modularly designed miniplant reactor system, planned and designed to simulate and optimize chemical reaction processes as well as mixing, dispersion and homogenization processes at a model scale with a maximum volume of 2000 ml.

Depending on the seal (FFPM), the medium in the reactor vessel can be heated up to 230 °C.

Vacuum operation is possible up to 25 mbar.

The IKA® laboratory software labworldsoft® is providing convenient solutions for measuring, control, regulating tasks and documentation purposes.

The system is planned and designed to simulate and optimize chemical reactions processes as well as mixing, dispersion and homogenization processes at a model scale.

Volume max.: 2000 ml

Volume min. (stirring): 500 ml

Volume min. (dispersing): 800 ml

Some applications are:

- Manufacturing cremes, lotions, emulsions
- Liposome preparations in the pharmaceutical and cosmetic sector
- Mixing solids such as calcium carbonate, talc, titanium oxide, etc. into liquid polymers
- Mixing additives and solid polymer compounds into mineral oils
- Grinding and disintegrating solids and fibres in liquids and polymers

LR-2.ST laboratory system consisting of:

- LR-2 Stand system
- EUROSTAR power control-visc P7: Laboratory stirrer with a high torque (380 Ncm), constant speed, digital display of rated - and actual speed, infinitely adjustable speed range 8 ÷ 290 min⁻¹, integrated torque trend display for viscosity control, RS 232 / analog interface
- LR 2000.11 Anchor stirrer with flow borings, without scraper

Please order reactor vessel separately.

Technical Data			
Usable volume min. [ml]	500	Usable volume max. [ml]	2000
Working temperature min. [°C]	room temp.	Working temperature max. [°C]	230
Pressure max. [bar]	1	Attainable vacuum [mbar]	25
Viscosity max. [mPas]	150000	Speed range [1/min]	8 - 290
Telescope stand stroke [mm]	390	Material in contact with medium [-]	borosilicate glass, FFPM, PTFE, steel 1.4571
Reactor vessel openings (units/standard) [-]	3/NS 29/32 2/NS 14/23"	Dimensions (W x H x D) [mm]	460 x 1240 x 430
Weight [kg]	25	Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80	Protection class according to DIN EN 60529 [-]	IP 42
RS 232 interface [-]	yes	Analog output [-]	yes
Voltage [V]	230	Frequency [Hz]	50/60
Power input [W]	130		